

Rheem Lazer[®] product data

Lazer [®] Boiling Water Unit		Lazer [®] Office		Lazer [®] Eco			Lazer [®] Commercial				
White		70103W-NZ	70105W-NZ	70303W-NZ	70305W-NZ	70307W-NZ	70207W-NZ	70210W-NZ	70215W-NZ	70225W-NZ	70240W-NZ
Stainless Steel		70103S-NZ	70105S-NZ				70207S-NZ	70210S-NZ	70215S-NZ	70225S-NZ	70240S-NZ
Capacity	Litres	3	5	3	5	7.5	7.5	10	15	25	40
Delivery – Initial	Litres	3.5	6	3.5	6	8.5	8.5	11	17	27	42
	Cups*	21	35	21	35	50	50	65	100	159	247
Recovery	L/hr	17.5	23	17.5	23	23	23	23	23	35	45
	– Cups per hour	103	135	103	135	135	135	135	135	206	265
Weight empty	kg	6	8	6	8	9	9	10	15	17	19
Weight full	kg	10	15	10	15	19	19	22	34	47	67
Min water pressure	kPa	50	50	50	50	50	50	50	75	75	100
Max water pressure	kPa	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000
Element Rating @ 240V	kW	1.8	2.4	1.8	2.4	2.4	2.4	2.4	2.4	3.6	4.6
Electrical connections		Supplied with 10 amp 3 pin plug and flex								Hardwired	
Plumbing connections		1/2" BSP									
Dimensions	mm										
A		285	334	283	336	336	336	336	336	336	490
B		209**	241**	160	192	192	192	192	299	299	340
C		435	465	435	465	515	515	615	515	720	615
D		–	–	280	312	312	312	312	419	419	460
E		65	65	65	65	65	65	65	65	65	65
F		70**	70**	45	45	45	45	45	45	45	45
G		33	33	50	50	50	50	50	50	50	50
H		20	20	23	23	23	23	23	23	23	23
M		142	167	142	168	168	168	168	168	168	245
N		174**	210**	238	270	270	270	270	377	377	418
Accessories		Part No.									
Lazer Eco Retrofit Mounting Bracket		-	-	318961	318962	-	-	-	-	-	-
Safety Tap		-	-	319069			319068				
5 Micron Remote Filter Kit		317327									

*Cup size 170ml

Calculations based on incoming water temperature of 18°C

**Includes 25mm for supplied backing plate

