

GAS STORAGE

Product		Outdoor Models		Indoor Models	
Rheem Gas Storage				441135NO	441170NO
Stellar [®] Gas Storage		850330NOZ	850360NOZ		
Approx. Storage Capacity	Litres	130	160	130	160
Recovery @ 45°C (Natural Gas)	Litres	200	200	110	126
**First Hour Capacity (Natural Gas)	Litres	330	360	240	286
Hourly Gas Consumption (Natural Gas)	MJ	42	42	29	33
kW Output	kW	10.5	10.5	5.8	6.6
Height	A (mm)	1600	1900	1555	1855
Width	B (mm)	485	485	430	430
Depth	C (mm)	558	558	515	515
	D (mm)	988	1213	N/A - Outlet on Top	N/A - Outlet on Top
	E (mm)	328	409	332	407
	F (mm)	298	298	300	300
	G (mm)	-	-	1475	1775
	H (mm)	-	-	75	75
Approx Weight Empty	Kg	70	80	50	69
TPR Valve Setting	kPa	1400	1400	1000	1000
Water Connections (LHS)		RP 3/4 /20	RP 3/4 /20	RP 3/4 /20	RP 3/4 /20
Gas Connection		RP 1/2 /15	RP 1/2 /15	RP 1/2 /15	RP 1/2 /15

**First hour capacity is a method of comparing the capabilities of different gas water heaters.
Please contact Rheem for actual hot water delivery for specific applications.

